



## UNLIMITED MOBILITY WITH BLUETOOTH® TECHNOLOGY

Featuring Bluetooth® Wireless Technology, the Gryphon GBT4100 readers eliminate the need for cables that limit operator movement and create safety concerns in the workplace. The reader can also transmit data to the host through its base station as well as to any commercial or embedded Bluetooth® v3.0 compliant device.

## HANDS-FREE OR PRESENTATION SCANNING WITH THE 2-POSITION CRADLE

Datalogic's unique 2-position cradle provides multiple features for the user. When in the 'up' position, this imager can be used as a hands-free or presentation style reader. With the Scan-While-Charging feature, there is never any concern about depleted or dead batteries, ensuring constant up-time for increased productivity.



## RELIABLE DATA COLLECTION

The Gryphon GBT4100 reader's batch mode capability allows more than 1200 bar codes to be stored in the memory. Combined with a 33,000 scans per charge Lithium-Ion battery, these two features create unlimited mobility and reliable data collection when out-of-range.

Datalogic's exclusive patented 'Green Spot' for good-read feedback helps to improve productivity in noisy environments or in situations where silence is required. When using the product with the cradle at a 45° position, the Green Spot can work as an aiming system to aid in positioning the bar code for quick and intuitive reading.



### FEATURES

- Fastest speed-to-read: 325 scans/second
- Bluetooth Wireless Technology with up to 30 m / 98 ft range
- Point-to-point and multi-point transmission
- Two-position cradle with Scan-While-Charging capability
- Batch Mode capability (>1200 codes stored in memory)
- Datalogic 'Green Spot' for good read feedback
- User-replaceable and long lasting Lithium-Ion battery
- Drop resistance to 1.8 m / 5.9 ft
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

### INDUSTRY-APPLICATIONS

- Retail: Point of Sale; Shelf Replenishment; Price Checking; Inventory
- Healthcare: Patient Tracking; Document Handling; Inventory; Bedside Scanning
- Commercial Services: Postal; Banks; Public Administration; Utilities; Document Handling

## TECHNICAL SPECIFICATIONS

### CORDLESS COMMUNICATIONS

**BLUETOOTH WIRELESS TECHNOLOGY** Protocol: Bluetooth 3.0 Certified Class 2  
Radio Frequency: 2.4 GHz  
Radio Range (Open Air): 30.0 m / 98.4 ft

### DECODING CAPABILITY

**1D / LINEAR CODES** Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.  
**POSTAL CODES** China Post  
**STACKED CODES** GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

### ELECTRICAL

**BATTERY** Battery Type: Lithium-Ion, 2100 mAh  
Charge Time: External Power (12 VDC): 4 Hours  
Reads per Charge: 33,000  
**CRADLE INDICATOR LEDS** Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)  
**CURRENT** Charging (Typical): < 8 W;  
Operating (Typical): < 2.5 W @ 5 VDC;  
Standby/Idle (Typical): < 2.5 mA @ 5 VDC  
**INPUT VOLTAGE** 4.5 - 14.0 VDC

### ENVIRONMENTAL

**AMBIENT LIGHT** 0 - 100,000 lux  
**DROP RESISTANCE** Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface  
**ESD PROTECTION (AIR DISCHARGE)** 16 kV  
**HUMIDITY (NON-CONDENSING)** 5 - 90%  
**PARTICULATE AND WATER SEALING** IP52  
**TEMPERATURE** Operating: 0 to 50 °C / 32 to 122 °F  
Storage/Transport: -20 to 70 °C / -4 to 158 °F

### INTERFACES

**INTERFACES** RS-232 / IBM 46XX / USB Multi-Interface;  
RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

### PHYSICAL CHARACTERISTICS

**COLORS AVAILABLE** Black; White  
**DIMENSIONS** Cradle: 18.6 x 9.9 x 5.6 cm / 7.25 x 3.9 x 2.2 in  
Reader: 18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in  
**WEIGHT** Cradle: 246 g / 8.68 oz; Reader: 225 g / 7.94 oz

### READING PERFORMANCE

**LIGHT SOURCE** Illumination: LED Array 630 - 670 nm  
**PRINT CONTRAST RATIO (MINIMUM)** 15%  
**READ RATE (MAXIMUM)** 325 reads/sec.  
**READING ANGLE** Pitch: +/- 65°; Roll (Tilt): +/- 35°; Skew (Yaw): +/- 65°  
**READING INDICATORS** Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED  
**RESOLUTION (MAXIMUM)** 0.076 mm / 3 mils

### READING RANGES

**TYPICAL DEPTH OF FIELD** Minimum distance determined by symbol length and scan angle.  
Printing resolution, contrast, and ambient light dependent.  
5 mils: 6.0 to 18.0 cm / 2.3 to 7.0 in  
7.5 mils: 3.5 to 30.0 cm / 1.4 to 11.7 in  
10 mils: 2.0 to 45.0 cm / 0.8 to 17.7 in  
13 mils: 3.0 to 60.0 cm / 1.2 to 23.4 in  
20 mils: 3.0 to 80.0 cm / 1.2 to 31.2 in

### SAFETY & REGULATORY

**AGENCY APPROVALS** The product meets necessary safety and regulatory approvals for its intended use.  
The Quick Reference Guide for this product can be referred to for a complete list of certifications.  
**ENVIRONMENTAL COMPLIANCE** Complies to China RoHS; Complies to EU RoHS  
**LED CLASSIFICATION** IEC 60825-1 Class 1 LED Product

### UTILITIES

**DATALOGIC ALADDIN™** Datalogic Aladdin configuration program is available for download at no charge.  
**OPOS / JAVAPOS** OPOS Utilities are available for download at no charge.  
**REMOTE HOST DOWNLOAD** Lowers service costs and improves operations: BC4010


### WARRANTY

**WARRANTY** 3-Year Factory Warranty

## ACCESSORIES

### Base Stations/Chargers

- BC4010-BK-BT Base/Charger, POS Multi-Interface, Black
- BC4010-WH-BT Base/Charger, POS Multi-Interface, White
- BC4030-BK-BT Base/Charger, Standard Multi-Interface, Black
- BC4030-WH-BT Base/Charger, Standard Multi-Interface, White
- CHR-GM40-BK Charging Only Base Station, Black
- CHR-GM40-WH Charging Only Base Station, White



### Batteries/Battery Chargers

- RBP-GM40 Removable Battery Pack

### Mounts/Stands

- 11-0360 Multi-Purpose Stand/Mount, Black
- 11-0362 Multi-Purpose Stand/Mount, Grey
- HLD-G040-BK Desk/Wall Holder, G040, Black
- HLD-G040-WH Desk/Wall Holder, G040, White
- STD-AUTO-G040-BK Smart Stand, G040, Black
- STD-AUTO-G040-WH Smart Stand, G040, White
- STD-G040-BK Basic Stand, G040, Dark
- STD-G040-WH Basic Stand, G040, White

