



POS-315 (with printer)



POS-314/315 (w/o printer)

A Compact & true All-in-One POS solution to delight your customers and boost your profits!

Salient Value



- Integrated high speed thermal printer with auto-cutter
- Compact design, Saves precious counter space
- Avoids messy connecting cables

- Powerful Intel® **DUAL CORE** processor
- **FANLESS**- Ideal for harsh, dusty environment
- Low power consumption



- Bright, rear side LCM Customer display for keeping your customers informed of progress of the transaction

- Magnetic Stripe Reader (MSR)
- Enables customer loyalty programs
- Speeds up Card transactions



- Tilting provision for Monitor & Customer display
- Accommodates any layout of retail counter



- Provision for displaying menu's & Promotions (for Printer models only)

- Wall mounting option
- Ideal for locations with space constraints



Technical Specifications

Model	POS-315	POS-314
CPU	Intel® DUAL CORE processor 1.86 GHz or higher	FANLESS FC CE
Storage memory	16 GB Solid State Drive (SSD) or 160 GB Hard disk or higher	160 GB Hard disk or higher
RAM	2 GB DDR3	
Display	15 inch TFT LCD, 1024 x 768, 250 nits	
Touch Panel	5-Wire Resistive	NA
Interfaces	2 x Serial (one powered), 1 x LAN, 1 x VGA	
Parallel port	NA	1
USB	6	
Audio	2 x 2 Watt Speaker	
Operating system Support	Windows® Embedded POSReady 2009, XP, Embedded POSReady 7, Windows®7 & Ubuntu Linux 11.10	
Integrated Printer (option)	Thermal printer with auto-cutter 80 mm paper width, 150 mm/sec printing speed	NA
Integrated MSR (option)	3-tracks MSR (USB) - OPOS Compliant	
Integrated Customer display (option)	CD-810: 20 x 2 LCM with backlight (RS-232 Serial) - OPOS Compliant	
External Peripherals (option)	Cash drawer, POS programmable Keyboard, Printer, Customer VFD Pole display	



Essae-Teraoka Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034
+91 80 3021 3000
+91 80 3021 3001

info@essae.com
http://www.essae.com
1-800-425-3111
0-78488 12346

47 Branches
Factories in Bengaluru and Goa
300 + Resellers

Essae®
...for Excellence