

- Equipped with Intel advanced CPUs
- green design with low power consumption
- IP54 dust & water proof
- Tool-free installation for stand



POS-385H

15" POS Terminal

Features



Dual LAN for data back-up and network access



Easy service & maintenance of HDD & components





Second Display 8.4" Touch



Covered side for optional I/O

POS-385H



Specification

Processor	Pentium DUAL CORE G850 2.9G, L2 3M, 65W
Chipset	Intel® H61
System Memory	2 GB DDR 3
Graphic Memory	Intel HD Graphics 3000/2000, integrated in CPU, frequency 850MHz (dynamic up to 1.1GHz)
LCD Panel	
LCD Size	15" TFT LCD
Brightness	250 cd/m ²
Resolution	1024x768
Touch Screen	Resistive
Tilt Adjustment	0° ~ 65°
Storage Device	
Hard Drive	160 GB or higher
Expansion	
miniPCI-E Socket	1
External I/O	
USB 2.0	4
Serial Port	4 x RJ45 COM ports (COM1 standard RS232; COM2 RS232/422/485; COM3/4 powered RS232; COM3 default 5V / COM4 default 12V by BIOS setting)
Parallel Port	1 (DB25 female)
GigaLAN (10/100/1000)	1 (RJ45) (H61)
DC Jack	1
VGA	1 (DB15 female)
Cash Drawer	1 (RJ11)
Audio Jack	1 x Line-out
Power	
Power Adapter	120W/19V
Control / Indicator	
Power Button	1
Indicator LED	1
Peripheral (option)	
MSR	3 Tracks MSR
Second Display	8.4" Touch
Customer Display	Flush mount VFD display 2 x 20 characters (COM)
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
OS Supported	
	Windows® XP, POS Ready 2009, XP Embedded, XP professional for Embedded, Linux, Windows® 7, POSReady 7

Essae-Teraoka Ltd.

410, 100ft Road, 4th Block,
Koramangala, Bengaluru-560 034

+91 80 3021 3000

+91 80 3021 3001

info@essae.com

http://www.essae.com

1-800-425-3111

0-78488 12346

47 Branches

Factories in Bengaluru and Goa

300 + Resellers

Essae®
...for Excellence