



## Features

- Powerful Intel Ivy Bridge CPU
- DDR 3 memory supports up to 32GB
- Windows 8.1 Industry Pro Retail
- Splash and dust resistant front bezel, IP66
- Engineered for Reliability
- Bezel Free and projective capacitive multi-touch
- Powered USB 12V\*1, 24V\*1
- Wall VESA mountable

The SP-1030, a high performance stylish POS system, offers several CPU choices including the Intel Celeron G540 2.5GHz dual core, i3 3.3GHz or the i5 3.0GHz processor. This processing power paired with a variety of peripheral options and Partner Tech's field approved quality provides the efficiency and the functionality required to deliver the future solution to meet all size retailers' challenging needs today.



# SP-1030

## POS Touch Terminal

# SP-1030

Item	SP-1030
CPU	Intel Celeron G540 2.5GHz Dual Core Ivy Bridge i3-3220 3.3GHz Dual Core Ivy Bridge i5-3550S 3.0 GHz Quad Core
LCD	15" Active TFT color LED LCD, resolution 1024 x 768
Touch	5-wire resistive touch (PS2 interface), bezel free/ Projective Capacitive (optional)
Memory	2GB Standard, Maximum 32 GB
Ethernet	IEEE 802.3 10/100/1000 BASE-T Gigabit Ethernet
Storage	SATA HDD, Second HDD (optional)
Interfaces	4 * COM ports (COM 1-2 powered with DC+0/5/12v, BIOS selection; COM3~4 powered with DC+0/5/12v jumper selection) 1 * DB-15 VGA port 1 * RJ11 port support two cash drawers (DC+24v) 1 *DC+12v out 4 *USB 2.0 2 *USB 3.0 1 *DC+12v input power-jack 1 * 12V Powered USB, 1 * 24V Powered USB (optional) 1 * DC +12V input power-jack
Magnetic Reader	Three track ISOs standard, encryption (optional)
Customer Facing Display	2x20 (9mm, 40 characters) Vacuum Florescent Display, 7" LCD bezel free style, 11.6" LCD and 15" LCD
Peripherals:	Biometric Reader, Smart card reader, RFID (NFC) reader for payment
Operating System	POS Ready7, Windows 7, Windows 8.1 Industry Pro Retail
Power Supply	AC100~240V/DC12V15A 180 watt power adaptor
Physical Dimensions	14.17" (W) x 9.44" (D) x 14.37" (H), (LCD 15 tilt angle)
Operating Temp	32°F ~ 104°F
Storage Temp	-4°F ~ 140°F
Humidity	15% ~ 80%
Certification	CE, FCC, LVD, VCCI, BSMI, 3C

\* specification subject to change without prior notice



SP-1030 with MSR (Optional)



SP-1030 with 2x20 VFD (Optional)



SP-1030 with CD-70 (Optional)



SP-1030 with PM-116 (Optional)



SP-1030 with PM-15 (Optional)



Peripheral Options



RP-600 Printer



Cash Drawer



Wide Tilt Angle