

XP-3200 Series

www.posiflex.com

POSIFLEX
Your Success is Our Vision



Specification	XP-3208H	XP-3212H
Processor	Pine View D525 1.8 G / 1 M Cache CPU (Dual Core)	
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB	
Storage Device	2.5" SATA HDD or SSD (Optional)	
Power Supply	12V DC power, 80W	
Audio	Buzzer only	
OS support	Win7 / Win XP Pro / POSReady 7 / POSReady 2009 / Linux	
Display		
LCD	8" TFT LCD, 800 x 600 resolution	12" TFT LCD, 1024 x 768 resolution
Touch Function	Resistive, 5-wire, USB Interface	
Brightness Control	By software control	
Tilt Adjustment	From 14° to 55°	
Connectivity		
LAN Port	10 / 100 / 1000 Mb	
Serial Port	DB9 x 2, RJ-45 x 1 (Optional RJ-45 to DB9 cable), with 5V support on COM2 / COM3, 12V support on COM2 / COM3	
PS/2 Keyboard	By internal cable (Optional)	
UPS Port	Yes, battery (Optional)	
Standard USB Port	4	
VGA Port	D-SUB, 15 pins, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR	
Printer		
Printer build in	2" Thermal Printer (60 mm / sec), 58 mm paper width	
Cutter	Manual	Auto cutter
Physical Dimension		
Dimension (W x D x H in mm)	325 x 386.2 x 249.6	
Weight (N. W. in kg)	4.15	
Environment		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
Options		
MSR	Integrated, 3 tracks and JIS-II	
PD-2605 / PD-2605U	2 x 20 VFD, default 200 mm pole	
PD-2606U	2 x 20 VFD, rear mount	
PD-309 / PD-309U	2 x 20 LCD, default 200 mm pole	
PD-330U	2 x 20 LCD, rear mount	
PD-76X4	240 x 64 dots Graphics LCD, default 200 mm pole	
SSD	8 GB Minimum	
LM/TM-2212	12" 2nd LCD Display or touch LCD Display with attachment SD-300	
UPS Battery	2300 mAh / 12V	
Certifications		

XP-3200 Series

Valued All-in-One Fan-Free POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.
** The product information and specifications are subject to change without prior notice.

2012XP32Q4C1

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

XP-3200 Series

Posiflex delivers the fan-free XP-3200 Series as valued all-in-one POS terminals. The all-in-one POS terminal XP-3200 Series combine touch screen, thermal printer, MSR in a fan-free system to bring retailers space-and-cost saving benefits. They are affordable in well-executed design for general purpose applications.

The XP-3200 Series are suitable for small and medium retailers to serve customers effectively.



Key Features

- ▶ Resistive touch screen : 8" TFT LCD 800 x 600 resolution, 12" TFT LCD, 1024 x 768 resolution
- ▶ Equipped with Intel Pine View D525 Dual Core 1.8 GHz and DDR3 memory
- ▶ All-in-one integrated system with touch screen, thermal printer and MSR for space saving
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Aluminum die casting design for efficient cooling
- ▶ 2" thermal printer with auto cutter (XP-3212H)
- ▶ Special "drop-load" design for easy printer paper roll loading
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ High quality, rock solid design with easy maintenance in mind

