

POSIFLEX

- Ultra-slim profile
- Highest build quality
- Robust performance
- Vast configurability



BB-3000
Bump Bar

PS-3315/3316

Kitchen Display System

PS-3315/3316

Model PS-3315/PS-3316

Processor	Intel Celeron N2807 processor, 1.58GHz/2.16GHz (Burst), 1M cache
System Memory	DDR3L 1333MHz SO-DIMM x 1, max. 4GB
Storage Device	2 x SATA Port (1 x SATA + 1 x mSATA) + 1 x eMMC connector
Power Supply	12V / 30W
OS Support	Windows 7 / POSReady 7 / Windows Embedded 8.1 Industry / Linux per request

Display

LCD Display	15" TFT LCD (PS-3315) ; 15.6" TFT LCD (PS-3316)
Resolution	1024 x 768 (PS-3315); default 1024 x 768, 1366 x 768 max (PS-3316)
Touch	5-wire resistive touch

Connectivity

Serial Port	4 x DB9, 5V/12V support on all COM ports
Parallel Port	1, via optional conversion cable
Standard USB Port	5
LAN Port	10 / 100 / 1000 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	1, via optional conversation cable
UPS Port	N/A
Audio	Buzzer only
Internal Expansion Slot	N/A

Physical Dimension

Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	5.6

Environment

Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH

Model BB-3000 BUMP BAR

Buttons	10-position programmable buttons. (Default: SERVE / RREV / RECALL / SIDE ON / SERVE / NEXT / RECALL / SIDE OFF + 2 x reserved button)
Communication	RS232
DIP Switch	8 segment DIP-switch for parameter changes
Operating Condition	Operation temp.: -25 to +70 Storage temp.: -30 to +80 Humidity: 10 to 90 %; 5 to 90 % (operation condition)

Note 1. Please note that this specification is pre-production spec, and is subjected to change without notice

Note 2. eMMC support requires WE 8.1 Industry; when eMMC functions as the boot device, it does not work with other SATA device(s)

Certifications



The product information and specifications are subject to change without prior notice.

2015G4



POSIFLEX Technology (India) Pvt Ltd., [India HQ]
985, 1st A Main Rd, 4th Cross, New Thippasandra, Bangalore 560 075.
Tel : +91 80 4078 2700 E-mail : Sales@posiflexindia.com
Fax : +91 80 4153 6089 Http://www.posiflexindia.com

POSIFLEX Technology Inc. [Global HQ]
Add No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan