



Z-3250

Handy Wireless CCD Scanner



Designed for optimal reading performance, the compact Z-3250 offers wide scanning range and wireless communication technology for easy handling of any applications. Z-3250 includes a 32-bit CPU and excellent scan engine in a small yet powerful unit delivering intuitive and rapid scanning regardless of environment.

- Compact, light weight and portable
- Compatible with iOS/Android devices and Windows PC
- 32-bit microprocessor
- Captures barcodes on mobile phone, tablet, or computer screens

1. Portability and mobility
2. iOS compatible
3. Antimicrobial housing available for medical usage



- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

OPERATIONAL

Light Source	617 nm visible red LED	
Optical System	Linear CCD array	
Microprocessor	32 bit	
Depth of Field	4 mil: 50 – 90 mm	5 mil: 50 – 120 mm
	7.5 mil: 30 – 210 mm	10 mil: 30 – 240 mm
	13 mil: 30 – 330 mm	20 mil: 40 – 380 mm
	<i>(Note: DOF may vary depending on environment condition and barcode quality)</i>	
Scan Rate	330 scans per second	
Min. Bar Width	4 mil	
Print Contrast	30% @ UPC/EAN 100%	
Indicator	Three-color LED (green, red & blue)	
Programmable Operation	Beeper tone & volume	
System Interface	USB HID, Virtual COM, OPOS	

PHYSICAL

Dimension	97.0 × 40.0 × 23.0 mm
Weight	79.7 g (battery included)

POWER

Input Voltage	5 VDC ±10%
Battery	3.7V, 850 mAh, Li-ion rechargeable battery
Operating Current	Charging: 440 mA; non-charging: 150 mA
Battery Life	Over 80 hours at 6 scans per minute (depending on condition)

RADIO COMMUNICATION

Radio Interface	RF wireless compatible with BT 2.1 SPP/HID profile mode
Working Range	Up to 100M (depends on operating environment)

REGULATORY

EMC	CE & FCC DOC compliant, VCCI, BSMI
-----	------------------------------------

ENVIRONMENTAL

Operating Temperature	0°C – 50°C (32°F – 122°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Level	0 – 100,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.2M drops
Environmental Sealing	IP43 rated sealing

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF 2 of 5, IATA Code, MSI, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, JAP, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Telepen
------------	---

